

# AQUATICA™

---

## Digital

### LENS CHART FOR CANON

For camera with 1:1 sensors

# TYPE 1





TYPE 1 FOR CANON

For Canon 1:1 & 1:3 sensors

### 4" dome port lens chart (# 18410)

Camera Lens	EXTENSION	Dome Shade	Zoom (Z) Focus (F) GEAR
Canon EF 15mm f/2.8 Fisheye	(*2)		
Sigma 10mm F2.8 EX DC HSM Fisheye	(*1)		
Sigma 15mm f/2.8 Fisheye	(*1)		
Tokina AT-X 10-17mm f/3.5-4.5 AF DX Fisheye	18456	Built in	(Z) 18722
Tokina AT-X 10-17mm f/3.5-4.5 AF DX Fisheye + 1.4x converter	18453	Built in	(Z) 18731

(\*1) Due to the length of the lens shade, it is impossible to use this lens with the # 18410 dome port  
 (\*2) Due to the minimum focusing distance being too far, it is impossible to use this lens with the # 18410 dome port

### 6" Dome port lens chart (#18409)

Camera lens	EXTENSION	DOME SHADE	Zoom (Z) Focus (F) GEAR
Canon EF 15mm f/2.8 Fisheye	Not Required	18484	(F)18702
Canon EF 20mm f/2.8	18456	18484	(F)18714
Sigma 8mm F3.5 EX DG Circular Fisheye	18456	Not Required	
Sigma 15mm F2.8 FISHEYE	Not Required	18484	(F)18715

Updated January 31, 2011



## Canon Type 1 lens chart

For Canon with 1:1 & 1:3 sensors

### 8" Dome port lens chart (#18405)

Camera lens	EXTENSION	DOME SHADE	GEAR
			Zoom (Z) or Focus (F)
Canon EF 14mm f/2.8 L <u>TYPE II</u> USM	18462	18480	(F)18771
Canon EF 14mm f/2.8 L <u>OLDER TYPE</u>	18453	18480	(F) 18713
Canon EF 15mm f/2.8 Fisheye	Not Required	18480	(F)18702
Canon EF 20mm f/2.8	18456	18480	(F)18714
Canon EF 16-35 mm f/2.8 L II USM	18457	18480	(Z)18708
Canon EF 16-35 mm f/2.8 L II USM (with manual focusing override*)	18464	18480	(Z)18708
Canon EF 17-40mm F/4L USM	18457	18480	(Z)18708
Canon EF 17-40mm F/4L USM (with manual focusing override*)	18465	18480	(Z)18708
Canon EF24-105mm f/4L IS USM (1)	18458	18480	(Z) 18700.1
Canon EF 24-70mm f/2.8L USM	18458	18480	(Z) 18723
Sigma 8mm F3.5 EX DG Circular Fisheye	18456	Not Required	Use in AF
Sigma 14mm F2.8 EX ASPHERICAL HSM	18462	18480	(F)18697
Sigma 15mm F2.8 FISHEYE	Not Required	18480	(F)18715

\* Focus gear is supplied with these dedicated extensions

(1) This lens requires a + 3 diopter to focus on the virtual image of the dome

### 9.25" Dome port lens chart (#18407)

BK-7 Coated mineral glass

Camera lens	EXTENSION	DOME SHADE	GEAR
			Zoom (Z) or Focus (F)
Canon EF 14mm f/2.8 L <u>TYPE II</u> USM	18462	INTEGRATED	(F)18771
Canon EF 14mm f/2.8 L <u>OLDER TYPE</u>	18453	INTEGRATED	(F) 18713
Canon EF 15mm f/2.8 Fisheye	Not Required	INTEGRATED	(F)18702
Canon EF 20mm f/2.8	18456	INTEGRATED	(F)18714
Canon EF 16-35 mm f/2.8 L II USM	18457	INTEGRATED	(Z)18708
Canon EF 16-35 mm f/2.8 L II USM (with manual focusing override*)	18464	INTEGRATED	(Z)18708
Canon EF 17-40mm F/4L USM	18457	INTEGRATED	(Z)18708
Canon EF 17-40mm F/4L USM (with manual focusing override*)	18465	INTEGRATED	(Z)18708
Canon EF 24-105mm f/4L IS USM (1)	18458	INTEGRATED	(Z)18700.1
Canon EF 24-70mm F2.8L USM	18458	INTEGRATED	(Z) 18723
Sigma 14mm F2.8 EX ASPHERICAL HSM	18462	INTEGRATED	(F)18697
Sigma 15mm F2.8 FISHEYE	Not Required	INTEGRATED	(F)18715

\* Focus gear is supplied with these dedicated extensions

(1) This lens requires a + 3 diopter to focus on the virtual image of the dome

Updated June 11, 2011



TYPE 1 FOR CANON

For Canon 1:1 & 1:3 sensors

## Macro port lens chart (# 18426 & 18428)

The 18426 AF/MF Macro Port is equipped with a focus knob that allows manual focusing when combined with a focus gear on the lens

The 18428 AF Macro port was designed to be operated in Autofocus mode

Camera Lens	18428 & 18426 EXTENSION	18426 FOCUS GEAR
Canon EF 50mm F2.5	18453	18705
Canon EF 100mm f/2.8 USM	18453	18700.1
Canon EF 100mm f/2.8 IS USM	18453	18700.1
Sigma 50mm F2.8 EX MACRO	18453	18701

## Macro port lens chart (# 18429)

The 18429 low profile macro port is designed to work with the 60mm EF-S but can also be used on other Macro lenses when combined with an extension

Camera Lens	Extension	Focus gear
Canon EF 100mm f/2.8 USM	18458	Not Available
Canon EF 100mm f/2.8 IS USM	18458	Not Available

Updated July 11, 2011